

## SPEED DOME CAMERA - 18X OPTICAL ZOOM

**SIDZL-18/48-24**



### FEATURES

- ▶ 1/4" ex-view CCD, Digital Signal Processing (DSP)
- ▶ High Resolution: 480TVL
- ▶ 18 x optical and 12 x digital zoom
- ▶ Minimum Illumination 0.01 Lux (1/3)
- ▶ Pan 360° endless with continuous rotation
- ▶ Tilt 0 - 90°
- ▶ 80 programmable presets
- ▶ Supports 16 tour sequences
- ▶ RS485 interface with multi-protocol support
- ▶ Built-in OSD user-friendly operation menu
- ▶ S/N ratio over 50dB
- ▶ PTZ display function
- ▶ Privacy mask

### DESCRIPTION

The Spectator PTZ speed dome camera is a compact high-speed unit with an integral receiver and camera/lens module. The speed dome is fitted with a 1/4" colour ex-view CCD. With its full 360° horizontal rotation and 0.5 - 300° / sec. speed, surveillance of any object is constant and continuous. Sleek indoor and outdoor housings make it ideal for various applications such as outdoor parking lots, town center surveillance, retail outlets, hotels etc.



**SPEED DOME CAMERA - 18X OPTICAL ZOOM****SIDZL-18/48-24****SPECIFICATIONS**

<b>Model</b>	<b>SIDZL-18/48-24</b>
Imaging element	1/4" Ex-View CCD
Horizontal resolution	480 TVL
Signal System	PAL / NTSC
Lens	18 x Optical zoom lens
Zoom	216 times (10 x optical x 12 x digital)
Viewing angle (Wide / Tele)	48° / 2.8°
Pan rotation range	360° endless
Pan Speed	0.5° ~ 300° / sec
Tilt view range	0 ~ 90°
Tilt Speed	0.5° ~ 150° / sec
Autopan	ON / OFF
Presets	80
S/N ratio	> 50 dB
Minimum illumination	0.7 Lux (Day only, 1/50)
AGC	Automatic
Alarm inputs	7
Alarm outputs	2
Iris control	Auto
Focus	Auto
BLC	ON / OFF
AWB	Automatic
Digital shutter	Auto : 1 ~ 1/10,000 sec
Baud rate (RS 485)	4800/9600/19200 bps
Power supply *	24 V AC
Operating temperature	-10°C ~ +50°C

\* Power Supply unit is not included and has to be ordered separately.

**DELIVERY PACKAGE**

- Indoor Speed Dome Camera

**ORDERNUMBERS**

- SIDZL-18/48-24 Indoor speed dome

