

SPEED DOME CAMERA - 18X OPTICAL ZOOM

SIFZL-18/48-24, SOFZL-18/48-24



FEATURES

- ▶ 1/4" ex-view CCD, Digital Signal Processing (DSP)
- ▶ High Resolution: 480TVL
- ▶ 18 x optical and 12 x digital zoom
- ▶ Minimum Illumination 0.01 Lux (1/3)
- ▶ Pan 360° endless with continuous rotation
- ▶ Tilt 0 - 90°
- ▶ 80 programmable presets
- ▶ Supports 16 tour sequences
- ▶ RS485 interface with multi-protocol support
- ▶ Built-in OSD user-friendly operation menu
- ▶ S/N ratio over 50dB
- ▶ PTZ display function
- ▶ Privacy mask

DESCRIPTION

The Spectator PTZ speed dome camera is a compact high-speed unit with an integral receiver and camera/lens module. The speed dome is fitted with a 1/4" colour ex-view CCD. With its full 360° horizontal rotation and 0.5 - 300° / sec. speed, surveillance of any object is constant and continuous. Sleek indoor and outdoor housings make it ideal for various applications such as outdoor parking lots, town center surveillance, retail outlets, hotels etc.



SPEED DOME CAMERA - 18X OPTICAL ZOOM**SIFZL-18/48-24 , SOFZL-18/48-24****SPECIFICATIONS**

| Model | SIFZL-18/48-24 SOFZL-18/48-24 |
|-----------------------------|---|
| Imaging element | 1/4" Ex-View CCD |
| Signal System | PAL / NTSC |
| Lens | 18 x Optical zoom lens |
| Zoom | 216 times (10 x optical x 12 x digital) |
| Viewing angle (Wide / Tele) | 48° / 2.8° |
| Pan rotation range | 360° endless |
| Pan Speed | 0.5° ~ 300° / sec |
| Tilt view range | 0 ~ 90° |
| Tilt Speed | 0.5° ~ 150° / sec |
| Autopan | ON / OFF |
| Presets | 80 |
| S/N ratio | > 50 dB |
| Minimum illumination | 0.01 Lux (Day/Night, 1/3) |
| AGC | Automatic |
| Alarm inputs | 7 |
| Alarm outputs | 2 |
| Iris control | Auto |
| Focus | Auto |
| BLC | ON / OFF |
| AWB | Automatic |
| Digital shutter | Auto : 1 ~ 1/10,000 sec |
| Baud rate (RS 485) | 4800/9600/19200 bps |
| Power supply * | 24 V AC |
| Operating temperature | -10°C ~+50°C -40°C ~+60°C |

* Power Supply unit is not included and has to be ordered separately.

DELIVERY PACKAGE

- Indoor / Outdoor Speed Dome Camera

ORDERNUMBERS

- SIFZL-18/48-24 Indoor speed dome
- SOFZL-18/48-24 Outdoor speed dome

